



# Opticalink

AR-4460PRO



# Opticalink

## AR-4460PRO

---

### Overview

Integrated with powerful interoperability and low cost, **XPON AR-4460PRO** WIFI6 ONT provide triple-play services to the subscribers in FTTx application.

Equipped with 1.25&2.5Gbps Downstream and 1.25Gbps Upstream XPON interface compliant with ITU-T G.984 standard, **AR-4460** ONT support the comprehensive triple-play services, including video and high-speed internet access service.



# Opticalink

## AR-4460PRO

### Hardware Specification



Parameter Name		Hardware Parameter	
Optical Interface	Optical Type	SC/PC	
	PON	Standard	ITU-T G.984 /ITU-T G.988 standard
		GPON Upstream 1.244Gbps, Downstream 2.488Gbps	
		Wavelength	Tx 1310nm, Rx 1490nm
		Sensitivity	Tx Range:0.5-5dBm Rx: >-28dBm
		Overload	>-8dBm
Interface Type	Ethernet Port	4*10/100/1000Base-T, Auto adaptive, Full/Half Duplex, RJ45 connector	
	WIFI	WiFi, <b>5dBi external antennas, 3000Mbps</b> , MIMO 2x2 2.4G, IEEE 802.11b/g/n/ax, 574 Mbps 5G, IEEE 802.11ac/ax, 2402Mbps	
Dimension		205mm(L)*136mm(W)*24mm(H)	
Weight		About 260g	
Power Supply		220V AC external power adapter, 12V/2A	
Power Consumption		<13W	
Working Environment	Temperature	-25°C to +55° C	
	Humidity	5% to 95% (no condensing)	

# Opticalink

## AR-4460PRO

---



### Software Features

Internet Connection – LAN – VLAN – Multicast – QoS  
L3 – Security – WiFi – OAM/OMCI





## Follow us in our Social Networks



[www.articfiberoptic.com](http://www.articfiberoptic.com)